HP Designjet Z6600 Production Printer



The fastest 60-in graphics production printer with efficient operation¹



Designed for speed and productivity

- Print as fast as 1500 ft²/hr (140 m²/hr) in fast mode and 212 ft²/hr (20 m²/hr) in high-quality mode²
- Cut turnaround times and effortlessly handle large data loads thanks to high file-processing power
- Create quality prints at top speed with HP Double Swath Technology and the HP Optical Media Advance Sensor
- Confidently print unattended thanks to heavy media rolls, 775-ml HP ink cartridges, and a built-in take-up reel

High-impact image quality

- Achieve smooth color tones thanks to HP Multi-Dimensional Smart Drop Placement Technology
- Create unique black-and-white prints—three shades of black HP ink deliver rich density and smooth transitions
- Offer your customers durable prints that last up to 200 years, using HP Vivid Photo Inks3
- Print a wide range of jobs—from posters, photos, and signs to canvas and backlit prints—on many substrates
- 1 Compared with large-format inkjet printers under \$25,000 USD for graphic applications. Based on the fastestrated color speeds as published by manufacturers as of October 2013. Test methods vary
- Using plain paper and fast mode, the HP Designiet Z6600 Production Printer can achieve speeds up to 1500 ft2/hr (140 m2/hr). Using glossy paper and normal mode, the Z6600 can achieve print speeds up to 212 ft2/hr

Efficient operation with a 6-ink printing system

- Print up to 30% more efficiently, using a 6-ink printing system with an optimized configuration4
- Choose how you want to print—send jobs right from your preferred design applications or through third-party RIPs
- Ensure image quality—and reduce cleaning and waste—using automatic drop detection and intelligent masking
- Gain color reliability with HP Professional PANTONE® color emulation and embedded Adobe® PostScript®/PDF5

Eco Highlights

- · Breakthrough color consistency can help reduce unnecessary reprints
- Free, convenient HP ink cartridge and printhead recycling
- FSC®-certified papers,2 range of recyclable HP media with a take-back program1





- Program availability varies. Please check hp.com/recycle for details. BMG trademark license code FSC®-C115319, see f<u>sc.org.</u> HP trademark license code FSC®-C017543, see f<u>sc.org</u>. Not all FSC®-certified products are available in all regions
- EPEAT registered where applicable/supported. See epeat.net for registration status by country

Please recycle large-format printing hardware and printing supplies.

Find out how at our website

- ³ Display permanence rating for interior displays/away from direct sunlight by HP Image Permanence Lab, and by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see global BMG.com/hp
- The HP Designjet Z6600 Production Printer uses 30% less ink than the HP Designjet Z6100 Printer (demonstrated by internal HP tests on glossy media in production mode).
- 5 HP Professional PANTONE color emulation and embedded Adobe PostScript/PDF upgrade kit sold separately



- 1. With Aurasma installed, please go to the HP Designjet channel at http://auras.ma/s/ke25m
- 2. Without Aurasma installed, please download it:
 - a. Google Play http://auras.ma/s/android
 - b. Apple Store http://auras.ma/s/ios

Once done, go to the HP Designjet channel at http://auras.ma/s/ke25m

3. Open the application and point to the image to view the HP Designjet video

Technical specifications

Best: 3.2 min/page on A1/D or up to 13.1 m²/hr (141 ft²/hr) on glossy media Normal: 2.1 min/page on A1/D or up to 19.7 m²/hr (212 ft²/hr) on glossy media on Up to 2400 x 1200 optimized dpi 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) Pigment-based HP Thermal Inkjet Cyan, magenta, yellow, light gray, matte black, photo black +/- 0.1% width 0.02 mm (0.0008 in) (HP-GL/2 addressable) 0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E)) width y Median < 1.19 dE2000, 95% of colors < 2.77 dE2000¹0 < 1 dE2000 in less than 5 minutes¹¹ nt-to- Average < 0.5 dE2000, max < 1 dE2000¹¹ ### 1.15 t* min/2.31 D¹² y Pall food nutratation that black and s		
Normal: 2.1 min/page on A1/D or up to 19.7 m²/hr (212 ft²/hr) on glossy media on Up to 2400 x 1200 optimized dpi 5 x \$ x \$ x \$ m (0.2 x 0.2 x 0.2 x 0.2 in) Pigment-based HP Thermal Inkjet Cyan, magenta, yellow, light gray, matte black, photo black +/- 0.1%³ width 0.02 mm (0.0008 in) (HP-GL/2 addressable) 0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E))³ width y Median < 1.19 dE2000, 95% of colors < 2.77 dE2000¹¹° < 1 dE2000 in less than 5 minutes¹¹ nt-to- Average < 0.5 dE2000, max < 1 dE2000¹¹¹ slility 4.5 L* min/2.31 D¹² y		
19.7 m²/hr (212 ft²/hr) on glossy media b) Up to 2400 x 1200 optimized dpi 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) Pigment-based HP Thermal Inkjet Cyan, magenta, yellow, light gray, matte black, photo black +/- 0.1% width 0.02 mm (0.0008 in) (HP-GL/2 addressable) 0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E))9 width y Median < 1.19 dE2000, 95% of colors < 2.77 dE2000¹0 < 1 dE2000 in less than 5 minutes¹¹ nt-to- Average < 0.5 dE2000, max < 1 dE2000¹¹ 4.5 L* min/2.31 D¹² y		
In Up to 2400 x 1200 optimized dpi 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) Pigment-based HP Thermal Inkjet Cyan, magenta, yellow, light gray, matte black, photo black +/- 0.1% width 0.02 mm (0.0008 in) (HP-GL/2 addressable) 0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E)) width Median < 1.19 dE2000, 95% of colors < 2.77 dE2000¹¹⁰ < 1 dE2000 in less than 5 minutes¹¹ nt-to- Average < 0.5 dE2000, max < 1 dE2000¹¹¹ d.5 L* min/2.31 D¹² y		
5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) Pigment-based HP Thermal Inkjet Cyan, magenta, yellow, light gray, matte black, photo black +/- 0.1% width 0.02 mm (0.0008 in) (HP-GL/2 addressable) 0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E)) width Median < 1.19 dE2000, 95% of colors < 2.77 dE2000¹0 < 1 dE2000 in less than 5 minutes¹¹ nt-to- Average < 0.5 dE2000, max < 1 dE2000¹¹ 4.5 L* min/2.31 D¹² y		
Pigment-based HP Thermal Inkjet Cyan, magenta, yellow, light gray, matte black, photo black +/- 0.1%° width 0.02 mm (0.0008 in) (HP-GL/2 addressable) 0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E))° width y		
HP Thermal Inkjet Cyan, magenta, yellow, light gray, matte black, photo black +/- 0.1%8 width 0.02 mm (0.0008 in) (HP-GL/2 addressable) 0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E))9 width y Median < 1.19 dE2000, 95% of colors < 2.77 dE200010 < 1 dE2000 in less than 5 minutes11 nt-to- Average < 0.5 dE2000, max < 1 dE200011 slitty 4.5 L* min/2.31 D12 y		
Cyan, magenta, yellow, light gray, matte black, photo black +/- 0.1%8 width 0.02 mm (0.0008 in) (HP-GL/2 addressable) 0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E))9 width y		
+/- 0.1% ⁹ width 0.02 mm (0.0008 in) (HP-GL/2 addressable) 0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E)) ⁹ width y Median < 1.19 dE2000, 95% of colors < 2.77 dE2000 ¹⁰ < 1 dE2000 in less than 5 minutes ¹¹ nt-to- Average < 0.5 dE2000, max < 1 dE2000 ¹¹ sility 4.5 L* min/2.31 D ¹² y		
width 0.02 mm (0.0008 in) (HP-GL/2 addressable) 0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E)) ⁹ width y Median < 1.19 dE2000, 95% of colors < 2.77 dE2000 ¹⁰ < 1 dE2000 in less than 5 minutes ¹¹ nt-to- Average < 0.5 dE2000, max < 1 dE2000 ¹¹ sility 4.5 L* min/2.31 D ¹² y		
0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E)) ⁹ width y Median < 1.19 dE2000, 95% of colors < 2.77 dE2000 ¹⁰ < 1 dE2000 in less than 5 minutes ¹¹ nt-to- Average < 0.5 dE2000, max < 1 dE2000 ¹¹ sility 4.5 L* min/2.31 D ¹² y		
0.067 mm (0.0026 in) (ISO/IEC 13660:2001(E)) ⁹ width y Median < 1.19 dE2000, 95% of colors < 2.77 dE2000 ¹⁰ < 1 dE2000 in less than 5 minutes ¹¹ nt-to- Average < 0.5 dE2000, max < 1 dE2000 ¹¹ sility 4.5 L* min/2.31 D ¹² y		
width y		
y Median < 1.19 dE2000, 95% of colors < 2.77 dE2000 ¹⁰ < 1 dE2000 in less than 5 minutes ¹¹ nt-to- Average < 0.5 dE2000, max < 1 dE2000 ¹¹ jility 4.5 L* min/2.31 D ¹² y		
< 1 dE2000 in less than 5 minutes ¹¹ nt-to- Average < 0.5 dE2000, max < 1 dE2000 ¹¹ jility 4.5 L* min/2.31 D ¹² y		
nt-to- Average < 0.5 dE2000, max < 1 dE2000 ¹¹ ility 4.5 L* min/2.31 D ¹² y		
4.5 L* min/2.31 D ¹² y		
Roll feed, automatic cutter, take-up reel		
Bond and coated paper, technical paper, film, photographic paper,		
proofing paper, backlit, self-adhesive, banner and sign, fabric, fine art printing material		
279 to 1524-mm (11 to 60-in) rolls		
Up to 0.56 mm (22 mil)		
ers, Mockups, Photos, Digital fine art, Banners, Exhibition, Event		
t boxes – film, Point of sale/display		
) ¹³ , 320 GB hard disk		
Gigabit Ethernet (1000Base-T), EIO Jetdirect accessory slot		
es HP-GL/2, HP-RTL, CALS G4		
es Adobe PostScript 3, Adobe PDF 1.7, TIFF, JPEG		
Printer driver, HP Embedded Web Server		
ded) HP-GL/2, HP-RTL drivers for Windows; PostScript Windows and Mac drivers with optional PostScript/PDF Upgrade Kit		
2430 x 690 x 1370 mm (95.7 x 27.2 x 53.9 in)		
2700 x 750 x 1200 mm (106.3 x 29.5 x 47.2 in)		
190 kg (419 lb)		
-		
251 kg (553.4 lb)		
Z6600 Production Printer, spindle, printheads, introductory ink cartridges cartridge, printer stand, take-up reel, 3-in spindle adaptor kit, quick		
de, setup poster, startup software, power cord 5 to 40°C (41 to 104°F)		
-20 to 55°C (-4 to 131°F)		
midity 20 to 80% RH		
re 53 dB(A) (printing); 39 dB(A) (ready); 39 dB(A) (sleep)		
7.0 B(A) (printing); 5.5 B(A) (ready); 5.5 B(A) (sleep)		
270 watts (printing); 420 watts (maximum); < 48 watts (ready); < 5 watts (sleep); < 0.3 watts (off)		
Input voltage (auto ranging): 100 to 127 VAC (+/- 10%), 5 A; 220 to 240 VAC (+/- 10%), 3 A; 50/60 Hz (+/- 3 Hz)		
USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina		
(IRAM), Mexico (NYCE), Korea (KATS)		
tic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand		
(RSM), China (CCC), Japan (VCCI), Korea (KC) al ENERGY STAR 2.0, WEEE, RoHS (EU, China, Korea, India), REACH,		
EPEAT Bronze		
One-year limited hardware warranty		

- Mechanical printing time. Printed in Fast mode with HP Vivid Photo Inks.
- Mechanical printing time. Printed with HP Vivid Photo Inks. +/- 0.1% of the specified vector length or +/- 0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on AO/E HP Matte Film in Best or Normal mode with HP Vivid Photo Inks. Measured on HP Matte Film.

- ICC absolute colorimetric accuracy with HP Vivid Photo Inks.
 With HP Premium Instant-dry Satin Photo Paper with HP Vivid Photo Inks, right after calibration.













_		
Product	F2S71A	HP Designjet Z6600 60-in Production Printer (not available in Latin America)
Accessories	CQ654C	HP Designjet HD Scanner
	CQ745B	HP Designjet PostScript/PDF Upgrade Kit
	CQ754A	HP Designjet 60-in Spindle
	J8025A	HP Jetdirect 640n Print Server
	Q6714A	HP Designjet 60-in Media Bin
	Q6715A	HP Designjet User Maintenance Kit
Original HP	C1Q20A	HP 773 Matte Black and Cyan Designjet Printhead
printheads	CE018A	HP 771 Magenta and Yellow Designjet Printhead
	CE020A	HP 771 Photo Black and Light Gray Designjet Printhead
Original HP	C1Q21A	HP 773A 775-ml Matte Black Designjet Ink Cartridge ¹⁴
ink cartridges	C1Q23A	HP 773A 775-ml Magenta Designjet Ink Cartridge ¹⁴
and maintenance	C1Q24A	HP 773A 775-ml Yellow Designjet Ink Cartridge ¹⁴
supplies	C1Q26A	HP 773A 775-ml Cyan Designjet Ink Cartridge ¹⁴
	C1Q27A	HP 773A 775-ml Photo Black Designjet Ink Cartridge ¹⁴
	C1Q28A	HP 773A 775-ml Light Gray Designjet Ink Cartridge ¹⁴
	B6Y15A	HP 771A 775-ml Matte Black Designjet Ink Cartridge
	B6Y17A	HP 771A 775-ml Magenta Designjet Ink Cartridge
	B6Y18A	HP 771A 775-ml Yellow Designjet Ink Cartridge
	B6Y20A	HP 771A 775-ml Light Cyan Designjet Ink Cartridge
	B6Y21A	HP 771A 775-ml Photo Black Designjet Ink Cartridge
	B6Y22A	HP 771A 775-ml Light Gray Designjet Ink Cartridge
	B6Y39A	HP 771A 3-pack 775-ml Matte Black Designjet Ink Cartridge
	B6Y41A	HP 771A 3-pack 775-ml Magenta Designjet Ink Cartridge
	B6Y42A	HP 771A 3-pack 775-ml Yellow Designjet Ink Cartridge
	B6Y44A	HP 771A 3-pack 775-ml Light Cyan Designjet Ink Cartridge
	B6Y45A	HP 771A 3-pack 775-ml Photo Black Designjet Ink Cartridge
	B6Y46A	HP 771A 3-pack 775-ml Light Gray Designjet Ink Cartridge
	CH644A	HP 771 Designjet Maintenance Cartridge
Original HP large format printing	Q8000A	HP Premium Instant-dry Satin Photo Paper (FSC® certified) ¹⁵ €3 ¹⁶ 1524 mm x 30.5 m (60 in x 100 ft)
materials	Q6578A	HP Universal Instant-dry Gloss Photo Paper (FSC® certified)¹5.4 mm x 30.5 m (60 in x 100 ft)
	Q8707A	HP Artist Matte Canvas 1524 mm x 15.2 m (60 in x 50 ft)
	Q8750A	HP Premium Vivid Colour Backlit Film ♣¹7 1524 mm x 30.5 m (60 in x 100 ft)

Service and support

H4518E HP Installation Service with Network Setup
U1ZM7E HP 2 years Next Business Day Onsite Support with DMR*
U1ZM8E HP 3 years Next Business Day Onsite Support with DMR*
U1ZM9E HP 5 years Next Business Day Onsite Support with DMR*
U1ZNOPE HP 1 years Post Warranty, Next Business Day Onsite Support with DMR*
U1ZN1PE HP 2 years Post Warranty, Next Business Day Onsite Support with DMR*
IIIXV4E HP Preventive Maintenance Service

* Defective Media Retention keeps your sensitive data safe. To comply with security regulations you can keep the defective hard-drive or data-retentive memory component while getting a new replacement disk or memory.

HP Designjet Support Services offer solutions for business critical environments — installation, extended support and maintenance, as well as variety of value-added services. For more information, please visit hp.com/go/designjet/support.

 $\label{thm:constraint} \textbf{Use HP Vivid Photo Inks and printheads to experience consistent high-quality and reliable performance} \\$ that enable less downtime and increased productivity. These critical printing system components are designed and engineered together to provide optimized efficiency, a wide color gamut, and prints with over 200 years fade resistance. 18 For more information, visit hp.com/go/Original HPinks

For the entire HP Large Format Printing Materials portfolio, please see globalBMG.com/hp.

- With HP Premium Instant-dry Gloss Photo Paper with HP Vivid Photo Inks.
- Based on 1 GB RAM. Expandable to 1.5 GB RAM through a Designjet qualified SODIMM included only in the optional HP Designjet PostScript®/PDF Upgrade Kit accessory.
- Only in selected US channels

 BMG trademark license code FSC®-C115319, see <u>fsc.org</u>. HP trademark license code FSC®-C017543, see <u>fsc.org</u>. Not all FSC®-certified products are available in all regions.
- In North America, recyclable in consumer collection systems that can accept mixed paper (may not be recyclable in your area)
- HP Large Format Media take-back program availability varies. Recycling programs may not exist in your area. See <u>hp.com/recycle</u> for details.
- Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media with Original HP inks. See globalBMG.com/hp.







For more information, please visit hp.com/go/DesignjetZ6600

© Copyright 2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe, PostScript, and Adobe PostScript 3 are trademarks of Adobe Systems Incorporated. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Windows is a U.S. registered trademark of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries.

